



REFLECTIVE THERMAL INSULATION

Prodex AP3 ALUMINUM FOIL + POLYETHYLENE FOAM + WHITE UV RESISTANT FACER

0.11 in thick closed cell polyethylene foam sandwiched between pure aluminum on one side and white polyethylene film on the other

Reflective thermal insulation developed according to the highest standards of quality, designed to save energy eliminating the radiant heat emitted by roofs, floors, and walls within the constructions.

Besides, it protects your home, business or project providing COMFORT at any time of year.



AP3 INSULATION (ALUMINUM FOIL + POLYETHYLENE FOAM + WHITE UV RESISTANT FACER)		
DIMENSIONS AND TOLERANCES OF THE STANDARD PRODUCT		
THICKNESS: 0.11 ± 0.008 (in)	LENGTH: ± 11 (in)	WIDTH: 4 ± 0.032 (ft)
TECHNICAL CHARACTERISTICS OF THE PRODUCT		
CHARACTERISTICS	VALUE	STANDARD
FOAM CELL STRUCTURE	CLOSED	-
EFFECTIVE WIDTH	3.83 FT	-
AVERAGE WEIGHT OF ft ²	0,028 lb/ft ²	-
WATER RESISTANCE	WATERPROOF	Dir. UEAtc
WATER VAPOR TRANSMISSION	0.05 perms (gr/ft ² *h*in.hg)	ASTM E 96/IRAM 1735
EMITANCE	0.03	ASTM C-1371-98
FUNGI RESISTANCE	NO GROWTH	ASTM C 1338
CORROSIVENESS	PASS	ASTM C-1224
PLIABILITY	NO CRACKING	ASTM C-1224
HUMIDITY RESISTANCE	PASS	ASTM C-1224
TENSILE STRENGTH AT BREAK (MD)	7.1 Lbf/inch	ASTM D -638
BLEEDING AND DELAMINATION	NO BLEEDING / NO DELAMINATION	ASTM C-1258
OPERATING TEMPERATURE	-4 °f / 176 °f	ASTM C-1224



- It is recommended a distance of 0 meters to 1.20 meters between supports
- Do not install at soffits when the insulation can be permanently exposed to UV radiation



PRODEX[®]
LEADERS IN THERMAL INSULATION FOR CONSTRUCTION

Ph (506) 2438-2322 | Fax (506) 2438-2341
www.prodexcr.com