



THERMAL INSULATION FOR WOOD-FINISH CEILINGS

Prodex RUSTIC ALUMINUM FOIL + POLYETHYLENE FOAM + UV RESISTANT WOOD-FINISH FACER

0.23" closed polyethyelene foam sandwiched between an reinforced aluminum layer on one side, and polyethylene UV-printed layer on the other

Reflective Thermal Insulation with a wood finish made of PRODEX closed-cell polyethylene foam with a single 0.23 in width. It is laminated with pure aluminum on one side and a polyethylene film

printed with a UV ink that provides insulation and beauty to your buildings.



Prodex Rustic APM6 C



Prodex Rustic APM6 O

- With a 1" and 0.11" thick space in the edge of the insulation roll to facilitate and improve the overlap between each piece.
- Use our exclusive system of HEAT-SEALED to make the joints of Prodex Rustic® and ensure a 100% waterproof seal.

APM6 INSULATION (ALUMINUM FOIL + POLYETHYLENE FOAM + UV RESISTANT WOOD-FINISH FACER)		
DIMENSIONS AND TOLERANCES OF THE STANDARD PRODUCT		
THICKNESS: 0.23 ± 0.017 (in)	LENGTH: 32.8 ± 11 (in)	WIDTH: 4 ± 0.032 (ft)
TECHNICAL CHARACTERISTICS OF THE PRODUCT		
CHARACTERISTICS	VALUE	STANDARD
FOAM CELL STRUCTURE	CLOSED	-
EFFECTIVE WIDTH	4 FT	-
AVERAGE WEIGHT OF ft²	0.054 lb/ft²	-
WATER RESISTANCE	WATERPROOF	Dir. UEAtc
WATER VAPOR TRANSMISSION	0.05 PERMS (gr/ft²*h*in.hg)	ASTM E 96/IRAM 1735
EMITANCE	0.03	ASTM C-1371-98
FUNGI RESISTANCE	NO GROWTH	ASTM C 1338
TENSILE STRENGTH AT BREAK (MD)	7.7 LbF/inch	ASTM D -638
OPERATING TEMPERATURE	-4 °f / 176 °f	ASTM C-1224



BEFORE



AFTER



Ph (506) 2438-2322 | Fax (506) 2438-2341
www.prodexcr.com