

TECHNICAL DESCRIPTION

Code: NT-101-P
Version: 1.0



DOUBLE-LAYER TERMOFLEX

Termoflex is bubble wrap plastic that comes in rolls and sheets to provide better protection of products.



ADVANTAGES

- Due to its versatility, it can be used for multiple applications
- TERMOFLEX bubble wrap protects fragile or delicate products from damage
- Resistant and economical
- TERMOFLEX bubble wrap eliminates empty spaces in boxes, avoiding damage of the contents

WRAP, PROTECT, AND SOFTEN AN IMPACT WITH **TERMOFLEX** BUBBLE WRAP



TERMOFLEX PACKAGING 3/16"

DIMENSIONS AND TOLERANCES OF THE PRODUCT

THICKNESS: 0,138 in +/- 10%

WIDHT: 4ft +/- 1%

LENGHT: 492 ft and 246 ft +/- 1%

TECHNICAL CHARACTERISTICS OF THE PRODUCT

CARACTERISTIC	VALUE	STANDARD
STRUCTURE	Bubble 3/16", 2 layers	-
COLOR	White	-
WEIGHT	68 g/m ²	-
TENSILE STRENGHT AT BREAK	5,5 N/cm	ASTM D 1623
COMPRESSION SET (24h at 25%)	90%	ASTM D5249
COMPRESSION RESISTANCE (25% DEFORMATION)	2,5 kPa	ASTM D5249

MADE IN COSTA RICA

Phone (506) 4001-5333 | E-mail info@termoflex.com